

SAFETY DATA SHEET

1. Identification

Important information *** This Safety Data Sheet is only authorised for use by HP for HP Original products. Any

unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action

being taken by HP. ***

Product identifier V1R34Series

Other means of identification

Synonyms HP 3D HR PA12 Powder

Recommended use Materials to be processed in HP 3D MJF equipment only.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

HP Inc.

1501 Page Mill Road Palo Alto, CA 94304-1112

United States

Telephone 650-857-5020

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209 (Direct) 1-760-710-0048

HP Inc. Customer Care

Line

(Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word Warning

Hazard statement May form combustible dust concentrations in air.

Precautionary statement

Prevention Take precautionary measures against static discharge. Use with adequate ventilation. Avoid

generation or accumulation of dust.

Response If inhaled, remove to fresh air. Get medical attention if symptoms persist. IN CASE OF FIRE, use

water spray or fog, foam, dry chemical or CO2. Collect in a chemical waste container. Use only

vacuum cleaners approved for combustible dust collection.

Storage Not available.

Disposal Not available.

Hazard(s) not otherwiseMay form combustible dust concentrations in air.

classified (HNOC) Risk of skin burns caused by hot melt.

GHS Supplemental information This material is considered hazardous under the OSHA Hazard Communication Standard criteria,

based on hazard(s) not otherwise classified.

3. Composition/information on ingredients

Mixtures

Material name: V1R34Series sps us

13842 Version #: 04 Revision date: 05-Jun-2019 Issue date: 06-Jun-2018

Chemical name % Common name and synonyms **CAS** number 90-100 Polyamide Proprietary This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard Composition comments Communication Standard). 4. First-aid measures Inhalation If dust from the material is inhaled, remove the affected person immediately to fresh air. Move to fresh air in case of accidental inhalation of vapors or decomposition products. If breathing is difficult, give oxygen. Oxygen or artificial respiration if needed. Consult a physician for specific advice. Wash the skin immediately with soap and water. In case of contact with molten product, cool Skin contact rapidly with water and seek immediate medical attention. Do not attempt to remove molten product from skin because skin will tear easily. Dust: Wash well-open eyes immediately, abundantly and thoroughly with water. Remove particle Eve contact remaining under the eyelids. If irritation persists, consult a doctor. On contact with hot product: Cool eyes rapidly with cold water after contact with molten polymer. Continue to rinse for at least 15 minutes. Get medical attention immediately. If swallowed, do NOT induce vomiting. Get medical attention. Never give anything by mouth to an Ingestion unconscious person. Most important No experiences of acute or chronic damages in humans have been made yet. symptoms/effects, acute and delayed **General information** Risk of skin burn caused by hot melt. Do not leave the victim unattended. Remove victim immediately from source of exposure.

5. Fire-fighting measures

Suitable extinguishing media
Unsuitable extinguishing

Water spray, foam, dry powder or carbon dioxide.

Do not use water jet as an extinguisher, as this will spread the fire.

Victim to lie down in the recovery position, cover and keep him warm.

Specific hazards arising from the chemical

media

May be released in case of fire: carbon monoxide, carbon dioxide, nitric oxides, organic products of decomposition. Under certain fire conditions, traces of other toxic products may occur.

Special protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire fighting equipment/instructions
General fire hazards

Do not use a solid stream of water. A solid stream of water can cause a dust explosion. Fire fighting equipment should be thoroughly decontaminated after use.

Dust clouds generated during handling and/or storage can form explosive mixtures with air. Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to free-fall or to be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact with the material or its container.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

In case product dust is released: Dust mask

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable container for disposal. If a vacuum is used, the motor must be rated as dust explosion-proof. Dispose of in compliance with federal, state, and local regulations.

Environmental precautions

Prevent further leakage or spillage. Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes Avoid breathing dust. Prevent dust accumulation to minimize explosion hazard. Inside and outside the equipment should be cleaned regularly with an explosion-protected vacuum cleaner to avoid dust accumulation. Do not sweep the dust or or try to remove it with a compressed-air gun. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

Conditions for safe storage, including any incompatibilities

Store away from moisture and heat to maintain the technical properties of the product. Eliminate sources of ignition. Do not expose to heat or store above 60C.

Material name: V1R34Series SDS US

8. Exposure controls/personal protection

Occupational exposure limits

Also see Exposure guidelines.

ACGIH

Material	Туре	Value	Form
V1R34Series	TWA	10 mg/m3	Inhalable particles (ACGIH)

Comments: Inhalable particles

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Exposure Limit For Dust

ACGIH (TWA/TLV): 3 mg/m3 (Respirable Particulate)
US CA OEL (TWA/PEL): 10 mg/m3 (Total dust)
US CA OEL (TWA/PEL): 5 mg/m3 (Respirable fraction)

US OSHA (TWA:Z-3): 15 mg/m3 (Total dust)
US OSHA (TWA:Z-3): 5 mg/m3 (Respirable fraction)

US OSHA (TWA:Z-3): 50millions of particles per cubic foot of air (Total dust)

US OSHA (TWA:Z-3): 15millions of particles per cubic foot of air (Respirable fraction)

Appropriate engineering controls

HP recommends the use of HP accessories for unpacking 3D parts and refilling the build chamber. If other methods are used, read the following: Dust clouds generated during handling and/or storage can form explosive mixtures with air. Dust explosion characteristics vary with the particle size, particle shape, moisture content, contaminants, and other variables. Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to fall freely or be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact with the material or its container.

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Consult ACGIH ventilation manual, NFPA Standard 91 and NFPA Standard 654 for design of exhaust system and safe handling.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields.

Skin protection

Hand protection Wear impermeable gloves. Protective heat-insulating gloves are to be used during thermal

processing. Any areas of skin covered with dust must be washed immediately with soap and water

as the powder draws out natural moisture from the skin. Use barrier cream regularly.

Other Processing of this product releases vapors or fumes which may cause skin irritation. It is a good

industrial hygiene practice to minimize skin contact. Wash thoroughly after handling.

Respiratory protection Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is

likely or airborne exposure limits are exceeded, use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during

processing.

Thermal hazards In thermal processing: Risk of skin burns. Wear appropriate thermal protective clothing, when

necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Powder. Solid.

Solia

Physical stateNot available.FormPowder.ColorWhite.

Odor Not available.

Material name: V1R34Series sps us

Odor threshold Not available.
pH Not available.

Melting point/freezing point 363.2 - 368.6 °F (184 - 187 °C)

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

ininability inint - app

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Solubility(ies)

Solubility (water) insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature $> 752 \,^{\circ}\text{F} \ (> 400 \,^{\circ}\text{C})$ Decomposition temperature $> 662 \,^{\circ}\text{F} \ (> 350 \,^{\circ}\text{C})$ ViscosityNot available.

Other information

Explosive properties Dusts might form explosive mixtures with air.

Powder explosivity data:

Minimum Ignition Energy (MIE) "dust cloud" w/ Inductance >30mJ.

Layer Ignition Temperature (LIT) "dust layer" >400degC. Minimum Ignition Temperature (MIT) "dust cloud" >360degC.

Auto Ignition Temperature (AIT) >400degC.

Flammability (flash back) This product is not flammable.

Oxidizing properties Not oxidizing.

Specific gravity 0.4 g/cm3

10. Stability and reactivity

Reactivity Under normal conditions: stable.

Chemical stabilityThe product is stable under normal handling and storage conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Take measures to mitigate material spillage and avoid potential ignition sources such as ESD

(ElectroStatic Discharges), flames, and sparks. Do not smoke nearby. Avoid wet/humid

environment. Recommended working humidity 50-70%. Avoid dust formation.

Incompatible materials Oxidizing materials, acids, strong bases, water and high humidity.

Hazardous decomposition

products

Decomposition products on thermal decomposition, carbon monoxide, carbon dioxide, Nitrogen

oxides (NOx), organic products of decomposition.

11. Toxicological information

Information on likely routes of exposure

Inhalation At high temperature, products of thermal decomposition can be irritating to respiratory system.

Skin contact May be considered as comparable to a similar product for which experimental results are: Non

irritating to skin.

Eye contact May be considered as comparable to a similar product for which experimental results are: Not

irritating to the eyes.

Material name: V1R34Series

intating to the cycs.

May be considered as comparable to a similar product for which experimental results are: Slightly Ingestion

harmful by ingestion.

Not available.

Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye

irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Based on available data, the classification criteria are not met. Respiratory sensitization Skin sensitization Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Based on available data, the classification criteria are not met. Reproductive toxicity

Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met. Complete toxicity data are not available for this specific formulation **Further information**

12. Ecological information

Ecotoxicity No ecotoxicity data noted for the ingredient(s).

Persistence and degradability Not available. Bioaccumulative potential Not available. Not available. Mobility in soil Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Do not allow this material to drain into sewers/water supplies.

Dispose of waste material according to Local, State, Federal, and Provincial Environmental

Regulations.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

ADR

Not regulated as dangerous goods.

Further information Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

Material name: V1R34Series SDS US

15. Regulatory information

US federal regulations US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

under TSCA

All ingredients are listed or exempt

US TSCA 12(b): Does not contain listed chemicals.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

No

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations Not Listed

Regulatory information All chemical substances in this HP product have been notified or are exempt from notification

under chemical substances notification laws in the following countries: US (TSCA), EU

(EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

16. Other information, including date of preparation or last revision

Issue date06-Jun-2018Revision date05-Jun-2019

Version # 04

Other information This SDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

Disclaimer This Safety Data Sheet document is provided without charge to customers of HP. Data is the most

current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other

countries.

This safety data sheet is meant to convey information about HP inks (toners) provided in HP Original ink (toner) supplies. If our Safety Data Sheet has been provided to you with a refilled, remanufactured, compatible or other non-HP Original supply please be aware that the information contained herein was not meant to convey information about such products and there could be considerable differences from information in this document and the safety information for the product you purchased. Please contact the seller of the refilled, remanufactured or compatible supplies for applicable information, including information on personal protective equipment, exposure risks and safe handling guidance. HP does not accept refilled, remanufactured or

compatible supplies in our recycling programs.

Revision information Identification: Important information

Material name: V1R34Series sps us

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name: V1R34Series sps us